



10/04/00

10-06-00

Please type a plus sign (+) inside this box [+]

PTO/SB/05 (12/97)

Approved for use through 09/30/00. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 004860.P2474Total Pages 2First Named Inventor or Application Identifier REID, GlennExpress Mail Label No. EL470494754US

ADDRESS TO: Commissioner for Patents
Box Patent Application
Washington, D. C. 20231

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. Specification (Total Pages 42)
(preferred arrangement set forth below)
 - Descriptive Title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claims
 - Abstract of the Disclosure
3. Drawings(s) (35 USC 113) (Total Sheets 10)
4. Oath or Declaration (Total Pages 5) (unsigned)
 - a. Newly Executed (Original or Copy)
 - b. Copy from a Prior Application (37 CFR 1.63(d))
(for Continuation/Divisional with Box 17 completed) (**Note Box 5 below**)
 - i. **DELETIONS OF INVENTOR(S)**. Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy or the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission(if applicable, all necessary)
 - a. Computer Readable Copy
 - b. Paper Copy (identical to computer copy)
 - c. Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. Assignment Papers (cover sheet & documents(s))
9. a. 37 CFR 3.73(b) Statement (where there is an assignee)
 b. Power of Attorney
10. English Translation Document (if applicable)
11. a. Information Disclosure Statement (IDS)/PTO-1449
 b. Copies of IDS Citations
12. Preliminary Amendment
13. Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. a. Small Entity Statement(s)
 b. Statement filed in prior application, Status still proper and desired
15. Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. Other: _____

Express Certificate of Mailing _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

Continuation Divisional Continuation-in-part (CIP)
of prior application No: _____

18. Correspondence Address

Customer Number or Bar Code Label (Insert Customer No. or Attach Bar Code Label here)
or

Correspondence Address Below

NAME Lisa Benado



10/4/00

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP

ADDRESS 12400 Wilshire Boulevard

Seventh Floor

CITY Los Angeles STATE California ZIP CODE 90025-1026

Country U.S.A. TELEPHONE (408) 720-8598 FAX (408) 720-9397

FEE TRANSMITTAL FOR FY 2000TOTAL AMOUNT OF PAYMENT (\$) \$ 1,104.00

Complete if Known:

Application No. New Application
 Filing Date October 4, 2000
 First Named Inventor REID, Glenn
 Group Art Unit Not Yet Assigned
 Examiner Name Not Yet Assigned
 Attorney Docket No. 004860.P2474

METHOD OF PAYMENT (check one)

- The Commissioner is hereby authorized to charge indicated fees and credit any over payments to:

Deposit Account Number 02-2666

Deposit Account Name _____

- Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17

- Payment Enclosed:

Check
 Money Order
 Other

FEES CALCULATION**1. BASIC FILING FEE**

Large Entity	Small Entity				
Fee	Fee	Fee	Fee	Fee Description	Fee Paid
Code (\$)	Code (\$)				
101 690	201 345			Utility application filing fee	<u>710.00</u>
106 310	206 155			Design application filing fee	_____
107 480	207 240			Plant filing fee	_____
108 690	208 345			Reissue filing fee	_____
114 150	214 75			Provisional application filing fee	_____
SUBTOTAL (1) \$					<u>710.00</u>

2. EXTRA CLAIM FEES

Total Claims	Independent Claims	Multiple Dependent	Extra Claims	Fee from below	Fee Paid
33			- 20** = <u>13</u>	X 18.00	= <u>234.00</u>
	5		- 3** = <u>2</u>	X 80.00	= <u>160.00</u>
					= _____

**Or number previously paid, if greater; For Reissues, see below.


Large Entity	Small Entity			
Fee	Fee	Fee	Fee	Fee Description
Code (\$)	Code (\$)			
103 18	203 9			Claims in excess of 20
102 78	202 39			Independent claims in excess of 3
104 260	204 130			Multiple dependent claim, if not paid
109 78	209 39			**Reissue independent claims over original patent
110 18	210 9			**Reissue claims in excess of 20 and over original patent
SUBTOTAL (2) \$				

FEE CALCULATION (continued)**3. ADDITIONAL FEES**

<u>Large Entity</u>	<u>Small Entity</u>	<u>Fee Description</u>	<u>Fee Paid</u>
Fee	Fee	Fee	
Code	(\$)	Code	(\$)
105	130	205	65
127	50	227	25
			Surcharge - late filing fee or oath
			Surcharge - late provisional filing fee
			or cover sheet
139	130	139	130
147	2,520	147	2,520
112	920*	112	920*
			Non-English specification
			For filing a request for reexamination
			Requesting publication of SIR prior to
			Examiner action
113	1,840*	113	1,840*
			Requesting publication of SIR after
			Examiner action
115	110	215	55
116	380	216	190
117	870	217	435
118	1,360	218	680
128	1,850	228	925
119	300	219	150
120	300	220	150
121	260	221	130
138	1,510	138	1,510
140	110	240	55
			Petition to institute a public use proceeding
			Petition to revive unavoidably abandoned
			application
141	1,210	241	605
			Petition to revive unintentionally
			abandoned application
142	1,210	242	605
143	430	243	215
144	580	244	290
122	130	122	130
123	50	123	50
126	240	126	240
581	40	581	40
			Petitions related to provisional applications
			Submission of Information Disclosure Stmt
			Recording each patent assignment per
			property (times number of properties)
146	690	246	345
149	690	249	345
			For filing a submission after final rejection
			(see 37 CFR 1.129(a))
			For each additional invention to be examined
			(see 37 CFR 1.129(a))
Other fee (specify)			
Other fee (specify)			
SUBTOTAL (3) \$ NA			

Reduced by Basic Filing Fee Paid*SUBMITTED BY:**

Typed or Printed Name: Lisa N. Benado

Signature Date *October 4, 2000*Reg. Number *39,999*Deposit Account User ID *02-2666*
(complete if applicable)**EXPRESS MAIL CERTIFICATE OF MAILING**"Express Mail" mailing label number: *EL672735056US*Date of Deposit: *October 4, 2000*

I hereby certify that I am causing this paper or fee to be deposited with the United States Postal Service "Express Mail Post Office to Addressee" service on the date indicated above and that this paper or fee has been addressed to BOX APPLICATION, Commissioner for Patents, Washington, D.C. 20231.

Kelli Ivey

Name of Person Mailing Paper or Fee *Kelli Ivey*Signature of Person Mailing Paper or Fee *10/4/00*

Date Signed

UNITED STATES PATENT APPLICATION

For

INTEGRATED TIME LINE FOR EDITING

Inventor:

Glenn Reid

Prepared by:

BLAKELY SOKOLOFF TAYLOR & ZAFMAN LLP

12400 Wilshire Boulevard
Los Angeles, CA 90025-1026
(408) 720-8598

Attorney's Docket No.: 004860.P2474

"Express Mail" mailing label number: EL672735060US

Date of Deposit: Oct 4, 2000

I hereby certify that I am causing this paper or fee to be deposited with the United States Postal Service "Express Mail Post Office to Addressee" service on the date indicated above and that this paper or fee has been addressed to the Assistant Commissioner for Patents, Washington, D. C. 20231

Kelli Tracy
(Typed or printed name of person mailing paper or fee)

Kelli Tracy
(Signature of person mailing paper or fee)
10/4/00

(Date signed)

DRAFT001 - 63308960

INTEGRATED TIME LINE FOR EDITING

NOTICE OF COPYRIGHT

A portion of the disclosure of this patent document contains material that is
5 subject to copyright protection. The copyright owner has no objection to the facsimile
reproduction by anyone of the patent document or the patent disclosure, as it appears
in the Patent and Trademark Office patent file or records, but otherwise reserves all
copyright rights whatsoever.

10 FIELD OF THE INVENTION

The present invention relates generally to methods for manipulating a time-based stream of information using a processing system, and more particularly to methods of using a user interface for editing a time based stream of information to create a presentation in a processing system.

15

BACKGROUND

There are many fields, such as entertainment, academics, business, health care, etc., that utilize media having time based streams of information. These time-based streams of information may be in the form of full motion images, e.g. video and
20 movies; audio, e.g. music, sound effects, and voice/narration; motion graphics, e.g. animation; still images, e.g. text, pictures; and combinations thereof. The information is usually comprised of a stream of individual units, e.g. frames or blocks. Frequently, this information is in a digital format and resides on any of a number of conventional electronic mediums.

25 Oftentimes, the time-based information is assembled into a presentation through the use of a processing system to edit the information. For example, a video may be edited and combined with audio, text, effects and/or graphics to create a presentation. A "presentation" is any changed version of an original time-based stream of information or a modified copy of the original information. In addition, a
30 "presentation" also may further be defined by at least one instruction for representing the original information in a changed form. In such an instruction-based presentation, the information is communicated in the manner according to the instruction. For Application

004860.P2474

instance, a software program may include directions on how a digital video should be played, where only certain frames of a video are chosen for display.

Digital editing typically is performed in a processing system and involves random retrieval of information from storage, communication of the information, e.g. display on a monitor, and manipulation of the information to produce the desired presentation. A portion or portions of sequential information, also referred to as a “clip,” such as a continuum of segments, frame, block or footage, may be rearranged into a desired order. Typically, the presentation appears as a seamless flow of the edited information. Editing may further entail removing portions of clips. During editing, particular “edit features” may be added to the presentation, such as transitions between clips, special effects (e.g., black and white, brightness, contrast, texture, echoes, compositing, blurring, etc.), text, graphics, black background, silent audio segments, combinations of different types of time-based streams of information, such as audio and still images, and the like. Various types of editing may be performed as new techniques for altering raw information are created.

Traditionally, editing of multimedia to produce presentations involved complex techniques performed by trained professionals. However, recently novice users have become interested in making presentations, as well. There has been increasing popularity in the processing of multimedia to produce sophisticated home movies, web sites, business presentations, amateur movies, etc..

Given the currently diverse level of skills among authors of presentations, it is desirable to provide processing a system that is easy and convenient to operate. Such a system should require less hands-on activity of the user and have a simple user interface display.

Although previous authoring systems provide for varying levels of ease for the novice user, there are still several drawbacks to these systems. Some prior systems include Studio DV from Pinnacle Systems Inc. of Santa Clara, California; Avid Cinema® from Avid Technology, Inc. of Tewksbury, Massachusetts; Adobe Premier® from Adobe of San Jose, California; Dazzle* Digital Video Creator™ from Dazzle Multimedia of Fremont, California; and DVgate™ from Sony Corporation of Tokyo, Japan.

In general, processing systems require that the time based stream of information be captured from a media source and entered into the system. The

information and the newly created presentation are stored within memory of the system.

The time based streams of information entered into the processing system consume an enormous amount of storage space within the system. For long presentations, such as business presentations or short film, the typical processing system provides an insufficient amount of storage space. For example, a 9 gigabytes hard drive that handles a sustained throughput of 5-7 megabytes/sec permits approximately a mere 40 minutes of video to be stored. Thus, it would be useful for a processing system to include enough storage space for a given presentation.

10 Typically, the presentation is in the form of references that correspond to the stored information. The references have instructions on handling the information. These processing systems permit the user to control what is viewed in the presentation by moving the in and out points in the references to indicate the segments of information that are to be accessed. Thus, a presentation may include instructions
15 regarding the portion of the information in which output is to begin and the portion of the information where the output is to cease. For example, the references may direct the select portions of the information that are to be included in the presentation. The references also may include edit features to be added to the presentation. In these instruction-based processing systems a user's edit choices are embodied by the
20 references.

25 Through a user interface, reference elements that represent selected clips that are to be included in a presentation are moved on the screen and displayed along extended windows, referred to as time lines or tracks. Such time lines represent the time course of a presentation and the position of each reference element on the time line dictates the order of the associated clip and edit feature in the presentation. Simple mechanisms to reposition the references onto appropriate positions of the screen would be beneficial for the user.

30 Prior systems generally have complicated user interfaces for edit of the time based stream of information. These processing systems display multiple time lines or tracks, where each time line is for the individual types of edit features to be included in a presentation. The separate time lines are usually oriented in parallel to each other. For example, as shown in **Figure 1**, a user interface **1** has a first time line **2** that contains a sequence of original clips **(1-3)** **3** along the first 3.00 minutes of the presentation. A second time line **4** has a clip with an edit feature **5** in the form of text

at minute 3.00 to 4.00. A third time line 6 has a clip with a special effect 7 at position 4.00 to 5.00 minute. These processing systems combines the information positioned along all of the time lines to form the presentation. Thus, in creating the presentation, the user works on each separate time line window for each type of attribute of the presentation. Where there is no single time line that integrates all attributes of the presentation, the user must mentally combine to all of the time lines to determine what the final presentation will be like.

A problem with these prior user interfaces is that the compounded time lines complicate the editing process for the user. In addition, the display of multiple time lines wastes screen real estate that may be better served to display other useful editing tools. Moreover, the data included in each time line is typically stored in separate areas of storage within the processing system. Thus, multiple time lines pointlessly consume precious storage space.

In light of the shortcomings of the various currently available systems, there is still a need for creating a presentation of a time based stream of information in a manner that is quick and easy to perform. In particular, there is a desire for a processing system that has a simple user interface that provides efficient use of screen display and storage by providing a single time line for editing of presentations. The system should also encompass convenient mechanisms to move data on the screen display.

SUMMARY OF THE INVENTION

In one embodiment of the present invention, a method for manipulating a time based stream of information in a processing system for generating a presentation is provided. The method allows for editing of references to the time based stream of information and positioning of the references along a time line. In one aspect of the method the processing system employed has functionality to provide only a single time line on a user interface for aligning references (depicted as reference elements) corresponding to visual time based stream of information. The time line is capable of handling references that include a variety of types of edit features, such as transitions between clips, special effects, text, graphics, black background, still images, combinations thereof, etc. Furthermore, these reference elements are moved around the user interface by user commands to drag and drop and/or cut and paste.

In some cases, the single graphical representation of a time line includes at least two references and it is desired to insert another reference having an edit feature between the two references. The edit feature reference may be nested by dragging its reference element to the time line in a position between the first and second present reference elements on the user interface. The second reference element shifts down the time line to make space for the inserted edit feature reference.

In various embodiments, the reference with the edit feature is provided by use of an edit box. The reference is moved to an edit box and the desired edit feature is attached to the reference in response to user edit commands. The reference element may be moved to the edit box by various means, such as dragging and dropping the reference element or by cutting the reference and pasting the reference over the edit box. Usually, placing the reference element in the edit box does not remove the reference element from its current location, such as its place on the time line, but rather enables editing of the reference by use of the edit box. A current edit feature of a reference may be optionally further edited by selecting the reference. An edit box automatically pops up on the user interface in response to this selection command.

The use of the single visual time line is direct in that the editing process is simplified for the user and space on the user interface as well as in storage is conserved. The various editing tools on the user interface are designed for ease of use.

Other features and advantages of these and other embodiments are discussed in detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention and its comparison with prior systems is illustrated by way of example, and not limitation, in the figures of the accompanying drawings in which:

5 **Figure 1** shows an exploded view of a user interface in a prior processing system having multiple time lines.

10 **Figure 2** illustrates one embodiment of an authoring environment in which a time based stream of information may be processed, in accordance with the teachings presented herein.

15 **Figure 3** is a block diagram of one embodiment of a processing system, configured in accordance with the teachings presented herein.

20 **Figure 4A – 4C** illustrates examples of various areas of storage, wherein **Figure 4A** shows one embodiment of an information storage area having clips of time based streams of information, **Figure 4B** shows one embodiment of a reference storage area and **Figure 4C** depicts one presentation storage area during generating of a presentation.

25 **Figures 5A – 5B** illustrate flow charts depicting methods for editing, in accordance with the present processes, wherein **Figure 5A** shows a method of cutting and pasting a portion of reference data and **Figure 5B** shows a method of adding an edit feature to reference data.

30 **Figures 6A – 6C** are examples of user interfaces for use in editing, according to one embodiment of the present invention, wherein **Figure 6A** is a GUI showing a reference icon, **Figure 6B** is a GUI showing controls for editing text into a presentation and **Figure 6C** is a GUI showing controls for editing transitions into a presentation.

35 **Figure 7** is a block diagram of a machine-readable medium storing executable code and/or other data to provide one or a combination of mechanisms for processing a time based stream of information, configured in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION

The methods described below are employed by an authoring tool configured to provide editing of a time based stream of information to generate a presentation. The processing system that may be utilized by the editing methods employs a user interface displaying references to the time based stream of information and other presentation attributes. Through the user interface, the system permits a user to easily control the editing process and select the information to be included in the presentation. The user interface has only a single time line for arranging various visual information to be included in the presentation. The system providing a solitary visual time line permits a conservation of storage areas allocated to the presentation.

The user interface also has simple mechanisms for moving references on the screen. One such component is a "drag and drop" control allowing the user to select references, drag them across the display screen and drop the references at some desired position, e.g. along the time line. In addition, a cut and paste edit component permits a user to select a reference, remove the reference from the display and paste it back onto any portion of the display.

The time based stream of information and related presentation created by use of the processing system may be of any form, such as full motion images with audio, full images without audio, audio only, still images, motion graphics or any combination thereof.

HARDWARE OVERVIEW

Figure 2 illustrates an exemplary authoring environment 10 in which a time based stream of information may be processed to produce a presentation. A processing system 12, according to one embodiment of the present invention, is in communication with an information source 80 that has a time based stream of information at a capture port 14 (i.e. information collection interface) and optionally through an intermediate digital converter 82. Processing system 12 may read, copy, manipulate, store, delete, output, print and/or transfer information provided by source 80. An optional external player 84 receives communication from processing system 12, either indirectly from a transfer port 16 and through pathway 86, and/or directly through a removable storage medium 18. Although **Figure 2** demonstrates one layout of authoring environment 10, the scope of the present invention anticipates any number of information sources and players, configured in accordance herewith and arranged in various fashions.

The information source **80** is any type of device that generates and transfers data or data signals related to the time based stream of information. The information source **80** may be a photographic or full motion image capture interface such as a camera, camcorder, digital camera, etc.; a sound capture interface, such as a laser disc player (e.g. CD player), tape player/recorder, MP3 player, microphone, etc.; a keyboard; a scanner; a computer; a server; a computer program; a sensor; any one of numerous available data collection devices; etc.

The information source may generate digital data signals and be communicatively coupled directly to the processing system **12**. Alternatively, the information source may generate signals in a format other than digital, e.g. analog signals. As shown in **Figure 2**, such non-digital data source may send signals to a digital converter **82** for changing the signals into a digital format prior to transfer of the data to the processing system **12**.

Communication between the information source **80** and the processing system **12** is often through means of a FireWire® (from Apple Computer, Inc. of Cupertino, California), iLink or IEEE 1394 communication protocol. Where a FireWire brand protocol is employed, capture port **14** in the processing system may be a six-pin FireWire brand port. Also, a corresponding four-pin FireWire brand port may be present on the digital converter **82**, where a digital converter is included, and/or on the information source **80**. In this case, a six-pin-to-four-pin cable may be used to connect the ports of the digital converter **82** or information source **80** and processing system **12**.

Other communication schemes are also suitable for transfer of data from information source **80** and/or digital converter **82** to the processing system **12**, such as an Ethernet connection (i.e., capture port **14** may be an Ethernet port), serial interfaces, parallel interfaces, RS422 and/or RS432 interfaces, Livewire interfaces, Appletalk busses, small computer system interfaces (SCSI), ATM busses and/or networks, token ring and/or other local area networks, universal serial buses (USB), PCI buses and wireless (e.g., infrared) connections, Internet connections, and other communication links for conveying the time based stream of information from an information source **80** to the processing system **12**. In addition, source **80** may store the information on a removable storage source, which is coupled to, e.g. inserted into, the processing system **12** and in communication with the capture port **14**. For

example, the source **80** may be a tape, CD, hard drive, disc or other removable storage medium.

Processing system **12** is any device configured to receive the time based information and manipulate the information to generate a presentation, e.g. a computer system or workstation. In one embodiment, the processing system **12** includes a platform **20**, e.g. a personal computer (PC), such as a Macintosh® (from Apple Computer, Inc. of Cupertino, California), Windows®-based PC (from Microsoft Corporation of Redmond, Washington), or one of a wide variety of hardware platforms that runs the UNIX operating system or other operating systems.

Often, the processing system **12** is configured to send the resulting presentation to an external player **84**.

The external player **84** may be an IP host, a computer, a personal digital assistance (PDA), a server, a tape/CD/MP3 player, or other device that is configured to receive presentation information from processing system **12** and to display the presentation. In one instance of an authoring environment, the external player **84** is the same device as the information source **80**, such as a camcorder. In still another case, no external player is provided and the presentation is played on the processing system and/or projected from the processing system onto a medium, e.g. a screen.

The external player **84** may receive information directly through removable storage **18** from the processing system **12**. Removable storage **18** represents any of a number of detachable storage mediums, e.g. magnetic, optical, magneto-optical, tape, and/or other type of machine-readable medium or device for storing information. For example, the removable storage **18** may be a hard disk, a read-only or writeable optical CD (e.g. CD ROM, DVD), a disc, tape, etc.

External player **84** may also receive presentation information indirectly from the processing system **12**, such as through a pathway **86**. The communication pathway **86** may be through various networking mechanisms, such as a FireWire brand connection(or iLink or IEEE 1394 connection), LAN, WAN, telephone line, serial line Internet protocol (SLIP), point-to-point protocol (PPP), an XDSL link, a satellite or other wireless link, a cable modem, ATM network connection, an ISDN line, a DSL line, Ethernet, or other communication link between the processing system and external player.

The processing system has components for handling time based information in various ways. As shown in **Figure 3**, these components include a capture port **14** for

acquiring the information, a storage **30** for holding the information, a processor **26** for manipulating the information, a process manager **66** for instructing the processor on editing and storage of information, a display **70** for showing a user interface and possibly a transfer port **16** or removable storage **18** for sending the information so

- 5 processed. Upon review of this specification, it will be appreciated by those skilled in the art that the components of processing system **12** may be connected in various ways in addition to those described herein.

Now referring in more detail to the components shown in **Figure 3**, processing system **12** includes processor **26**, which may represent one or more processors. Some 10 exemplary processors are a Motorola Power PC processor, an Intel Pentium (or x86) processor, etc. The processor **26** may also be a microprocessor. The processor **26** runs an operating system and applications software that controls the operation of other system components.

Storage **30** is coupled to processor **26** by a bus **22**. The storage **30** may be a 15 dynamic random access memory (DRAM) and/or may include static RAM (SRAM). Typically the storage is a hard disk drive, but may alternatively be another magnetic disk, a magneto-optical disk or other read/write device. The processor may also be coupled to other types of alternative storage areas that may be considered as part of the storage **30** or separate from the storage **30**. Such alternative storage areas may 20 include cache, flash memory, etc., and which may also be considered the removable storage **18**. Usually storage **30** has a capacity in the megabyte to gigabyte range, and more typically, at least 2 gigabytes capacity and can sustain throughput of at least 3.5 megabytes per second of information. However, as technology advances, the capacity of the storage may increase. The storage **30** contains the acquired time based stream 25 of information within files as well as executable code that provides functionality for processing the time based stream of information in accordance with the present invention. The storage also has at least one and usually multiple references to the stored information. The reference includes data, e.g. instructions, on how the processor is to read and/or manipulate the stored information. Typically, a reference is 30 an object that corresponds to individual clips of information. The reference data include at least one in-point that specifies where the processor is to start accessing the stream of information and at least one out-point that identifies where to stop access of the information. The reference may also contain instructions on adding particular edit features to a presentation that are in addition to the stored information. Some edit

features are text, transitions, graphics, special effects, overlays, three-dimensional images, audio, etc. and location data on where such edit features are to be presented in the time based stream of information. Edit features are any of various modifications to the original information for use in the presentation that exist with current editing technology or may be created in the future.

The time based stream of information is stored within files in an information storage area **50**. One exemplary information storage area **50** is depicted in **Figure 4A** as having a segment of a time based stream of information, clip A **100** with units (0 to 50), and another fragment, clip B **110** having units (0 to 30).

The storage also has at least one and usually multiple references to the stored information in a reference storage area **52**. One embodiment of reference storage areas **52** representing an edit is shown in **Figure 4B**, where reference storage area **52** corresponds to the information of **Figure 4A** with modified reference A1 (0 to 20) **106** corresponding to clip A, but only from units (0 to 20) **100**, a copy reference A2 (0 to 50) **104** and reference B (0 to 30) **112** corresponding to clip B units (0 to 30) **110**.

The presentation that is generated by the processing system, as represented by the references, is stored in presentation storage area **54**. The presentation storage area includes data related to when the information is to be displayed along a presentation time line **56**. One presentation storage area **54** that draws upon the pool of reference data from **Figure 4B** is shown in **Figure 4C** and begin with reference A1 (0 to 20) **106** corresponding to clip A units (0 to 20) **100** and immediately followed by reference B **112** corresponding to clip B units (0 to 30) **110**.

A reference database **32** within the storage **30** contains an index of the stored references. Each entry **34** in the database is to a reference. The database contains data found within the reference such as clip **36**, in-point **38** and out-point **40**. For example, a reference 1 may indicate clip A with an in-point at frame 0 and out-point at frame 60. The database may also include other reference data that assists in generating a presentation.

Further to the storage **30**, an optional trash depository **58** may be included to temporarily hold references, reference data, the time based stream of information, or any portions thereof. The contents of the trash depository may be accessed, manipulated, or removed by the processing system. Often, the trash depository **58** serves as a holding bin for unwanted data prior to its deletion from storage. By dropping the data into the trash depository, the user may continue with uninterrupted

editing and later empty the trash, i.e., delete the contents and any associated information, at a convenient time.

A process manager **66** is coupled to storage **30** and processor **26** through bus **22** for carrying out various tasks that control the edit and storage of information and reference data. During the capturing of information, process manager **66** may allocate space on the storage for keeping a new information file. The process manager receives selection commands, such as from a user input or software instructions, and responds by selecting the appropriate information and/or reference data, which may be an entire file of information/data or portions thereof. The commands may be provided by a user selecting reference data, where the selected data may be an entire reference or a portion of the reference. The selected information may also include several files of information/data. As shown variously by the flowcharts in **Figures 5A** to **5B**, the process manager carries out edit commands by modifying the reference data and/or information in storage.

15 (1) Cut and Paste Editing

Figure 5A shows an example of a method of cutting or copying a portion of a clip during the processing of a presentation. A first reference is initially provided **120**. For example, reference A1 corresponding to clip A (0 to 50) is presented. Next, the processing manager copies the reference. For example, reference A1 is copied to **20** create a duplicate reference A2 (0 to 50) **122**. The process manager changes the reference data of either the original or copied reference to reflect edit command requests. In the example, the in point and out point of reference A2 are modified to (0 to 20) **124**. The process manager places modified reference onto a paste board **126** for inserting into a presentation. The reference data that is present in the paste board **25** may be inserted at any point in the presentation along the time line in presentation storage area **54**. Where the reference is to be placed prior to or after another reference already present in the presentation storage area, or if there are no other references provided in the presentation storage area, the reference is simply pasted into the storage area **136**. If the reference is to be placed within another reference, the other reference is first split **128** by copying the other reference **130** and modifying the in and out points of the other reference and its copy to reflect the split **132**. The modified reference A is then pasted between the two reference B's in the presentation storage area **134**.

In the example, reference A2 is moved to a paste board file in storage. The presentation storage area has a third reference B1 (0 to 30). Reference A2 is intended for a position after unit 15 within reference B1 (0 to 30). To accomplish the nesting of reference A2 within reference B1, the data in reference B1 is split. Reference B1 (0 to 30) is copied to create reference B2 (0 to 30). The in and out points are changed so that the reference B1 (0 to 15) corresponds to the first clip portion prior to the inserted reference A2 and the reference B2 (16 to 30) corresponds to the second clip portion following reference A2. Reference A2 is then placed after reference B1 along the time line in the presentation storage area 56.

- 10 In subsequent steps, the cut and paste process may be undone to retrieve the original data. In the example described in **Figure 5A**, reference A2 may be deleted in response to a deletion command and reference A1 is preserved. The continuum time line between reference B1 and B2 is also restored such that there is no gap where reference A2 had previously been positioned. Although referenced B1 and B2 may 15 remain split, the two references run seamlessly to appear as though there is a single reference to the clip.

(2) Adding Edit Features

- 20 **Figure 5B** shows an example of a method of adding edit features to a clip during the processing of a presentation. A reference is initially provided 138 and then copied 140. Usually, selected edit features may be added to either the beginning or ending portions of the clip represented by the original or the copy reference 142. Where the edit feature is intended for the beginning or ending unit(s) of a reference, the feature is simply inserted in the reference 144 and the reference having the edit 25 feature is placed in the presentation storage area 146. Movement of the reference may be through the cut and paste methods described above or by a user command to drag and drop the reference in place.

For example, to add an edit feature, a reference A1 corresponding to clip A (0 to 50) is provided. The reference A1 is copied to create a duplicate reference A2 (0 to 50). The reference A1 may be modified to insert text to the beginning portion of the 30 clip (first frame) or to the ending portion of the clip (last frame).

In the alternative, text may be added to a middle portion of a clip, as shown in **Figure 5B**. The reference that is targeted for text editing is split at the location for the text 142 by copying the reference 148 and modifying the in and out points of the reference and its copy to reflect the split 150. The text may be added to the beginning

unit(s) or ending unit(s) of the split reference 152 and the edited reference added to the presentation storage area 154. In the example where text is added to reference A2 (0 to 50), reference A2 (0 to 50) is split at the point in which text is to be added to form reference A2(a) (0 to 25) and reference A2(b) (26 to 50). The text may be added 5 to the last unit of reference A2(a) at 25 and may additionally be included in any sequential units previous to 26 without skipping any units in the timeline. It is also possible to add the text to reference A2(b) starting at unit 26, and to any sequentially following units without skipping any such units.

10 The methods described in **Figure 5A and 5B** may also be applied to adding any time of editing features to the presentation in addition to text, such as transitions, audio, graphics, etc.

15 At times, an edited version of the time based stream of information may be produced by the system and stored. The time based stream of information that corresponds to an edited reference is copied into storage. Then, either the original or copy of the information is modified to reflect the edited reference. Thus, the storage includes both the original time based stream of information and edited version of the information.

20 Further to the edit capabilities of the processing system, the system may receive a trash and/or delete command, such as from a user input or software instruction. The process manager 44 may respond to the delete command by deleting the relevant information and references thereof. Furthermore, where the selected data is cut and placed onto a paste board, the process manager may respond to a delete command by deleting the data from the paste board and as well as its associated information.

25 Such deletion may be by the process manager directly and permanently eliminating the selected information (and associated reference data) from storage. Such direct elimination may take place by the process manager copying over the relevant file. If there is any information occurring prior to or after the eliminated section, the remaining information appears to be continuous and uninterrupted by the 30 copy over the excluded section. In the alternative, the deletion may also take place by changing a virtual file allocation table (VFAT, FAT or FAT32) to indicate that the space that has been used by that file is available for reuse by another file. When new files are written to that space, the deleted data is overwritten and thus, permanently

eliminated. Prior to this overwriting, it may be possible for the deletion to be reversible.

In one embodiment, direct elimination of information occurs where the beginning portion or middle portion of a clip in a file is selected for deletion. This 5 elimination may occur by various mechanisms. In one embodiment, the system may copy the portion that is to be preserved into a new file and the old file may be removed. In another instance, the system may simply shift over the preserved data to replace the eliminated data. For example, where units 0-30 are to be eliminated from a clip of 0-40, units 31 to 40 may be moved into the space previously occupied by 0-30, 10 thus creating a clip 0-9. In this manner the header information that may be present in the beginning of a clip may also be preserved.

Where a tail end of a clip in a file is to be deleted, the clip may be merely truncated such that the ending portion is marked as extra space that is available for reuse. Thus, the beginning header information is still present in the file. Furthermore, 15 5 in order to erase all of a file that is selected for elimination, the deletion may take place by merely marking the entire file as deleted and available for reuse as described above.

In any case, the process manager may also be triggered to perform several relevant routines upon receipt of the delete command. In one embodiment, a reference 20 25 check method is performed when the system receives a selected information command and a delete command. The process manager responds to the delete command by checking in the reference database to determine if a single or no reference data to the selected information exists. Where the process manager concludes that more than one reference data set to the selected information exists, the process manager fails to eliminate the selected information from storage. Rather than deleting the information from storage, only the selected reference data is deleted. On the other hand, if the process manager establishes that more than one reference data set to the selected information does not exist, the process manager deletes the selected reference data contained within a reference or portion of a reference, if any are such 30 data present in the storage, and also deletes the selected information from storage.

In some embodiments of the processing system, a trash procedure is performed by the process manager. The system receives a selected information command and a trash/delete command, such as from a user input or software instructions. In response, the process manager extracts the selected reference data,

which may be an entire reference or selected portion of a reference and places it into a trash depository. At any time while the reference data is in the trash depository, the processing system may receive a cancel command, such as from the user or other means. In the case of a cancel command, the process manager returns the reference
5 data back to its original location and restores the initial reference, e.g. in and out points, rather than deleting the reference and the information. Where the processing system receives a trash/deleted command and no cancel command is received, the process manager then may either delete the information and associated reference data, or in the alternative, respond to the delete command by performing the check
10 procedures from step describe above in which the contents are deleted if more than one reference data is not found.

The total amount of storage space available for new files is determined by a space monitor **68**. Space monitor **68** is coupled to storage **30** through bus **22**. When a new file is created to hold information, the space monitor ascertains the amount of space that is utilized by the new file and subtracts this consumed space to recalculate
15 the remaining amount of space in storage.

In the processing system **12**, the processor **26** is further coupled by bus **22** to an input/output (I/O) control **90**, a transfer port **16** and/or removable storage **18**. The I/O control **90** commands one or multiple I/O device(s) **92**. Some conventional I/O devices are key boards, mouses/trackballs or other pointing devices, microphones, speakers, magnetic disk drives, optical disk drives, printers, scanners, digital cameras, etc.

In one configuration of processing system **12**, a means for communicating with an information source that has a time based stream of information is provided.
25 For example, bus **22** additionally couples detector **24** to the processor **26**. The processing system may detect a connection between the processing system and the information source through detector **24**. The detector **24** performs an inquiry as to whether an information source is in communication with the processing system. The detector determines a connection with the information source by sensing particular
30 signals, such as electrical current output, that are released from the information source, and usually when the source is energized, i.e. "turned-on." The detector may be further configured to conduct periodic checks for communication with the information source.

Further to the details of platform 20 in **Figure 3**, a display control 74, e.g. video board, is coupled to the processor 24 also through bus 22. The display control 74 communicates with the display 70 in the processing system 12 to couple the display 70 to the platform 20. Display 70 may be any one of a number of conventional display devices such as a liquid crystal display, cathode ray tube, plasma display, video display, or other type of display device. For sharp colors and grayscale, display 70 may be an SVGA monitor, with a resolution of 800 x 600 (26 dpi) or better, with an active area of at least 15 inches, and may be controlled using a true color video card.

Means are provided for capturing the time based stream of information from the information source, such as a capture card or other capture mechanisms. The transfer rate of the information entering the system is usually the same or substantially the same speed that the information runs prior to entering the system, such as the rates established by the video standards of various regions. For example, movie film usually runs with a speed of 24 fps. Some video follows the NTSC (system used in North America and Japan), where the video speed is 30 fps.

The information may be captured and written into storage by various mechanisms. One capture mechanism is a sequential-type method in which an application procedure is executed when the processing system is in capture mode. In one stage of the application procedure, signals from an information source are captured. The system reads the information, shows the information on the display and writes the information to a storage medium. However, when control elements are activated, the system moves away from the capture step and switches to another stage that includes a process control commands loop for handling the control instructions. The CPU of a system employing such a sequential-type method is dedicated to processing the control commands. While application procedure is in the process control command loop, the capturing operation ceases and the processing system stops communicating with the information source. During this period, the information that is released from the information source does not get loaded into the system. Rather, the processing of control commands continues through to completion, at which time, the capturing step may continue.

Another capture mechanism, according to the present invention, is a low-level interrupt-type method, which effectively permits intermittent processing of control element commands while, at the same time, loading the time-based information. With

the interrupt-type method, in addition to the capture application, a user may run any software applications, e.g. network communication protocols, such as Appletalk, Internet or e-mail applications, word processing applications, etc.

An interrupt-type method includes an application procedure that may be

- 5 executed when the processing system is in capture mode and when it is not in capture mode, e.g. when the system is in edit mode. Where the processing system is operating in a non-capture mode, the application procedure conducts normal operations, such as processing of control commands from control elements. However, when the capture mode is indicated, the interrupt procedure fires the appropriate capture tasks and
10 causes a temporary suspension of the application procedure in an asynchronous manner. Thus, the processing of control commands proceeds until the capture process interrupts the other application tasks.

This interrupt procedure may be performed at periodic intervals and are certain to iterate at regular times, despite the activities, e.g. processing of control

- 15 commands, of the application procedure. The interrupt procedure includes a quick reading of incoming information, copying the information into a proxy, outputting the information and writing it into storage where the information may be further edited by use of the control elements. The interrupt procedure is advantageous in that the process is very quickly performed and rapidly repeats. The time for performance is
20 less than the transfer rate of the information entering the system.

The repetitions of the interrupt procedure occur at a rate that is substantially similar to or the same as the transfer rate. Thus, all of the information may be read and stored while still processing control commands in-between each of the iterations of the interrupt procedure. As a result, the user does not recognize the interruptions

- 25 and the capture process as well as other instructions appear to be simultaneously executed by the system. Moreover, the interrupt procedure guarantees that information is not omitted from the reading step because the iterations of the interrupt procedure and length of time to perform are timed to correspond with the rate of information transfer from the information source.

- 30 For transfer of NTSC video, the interrupt procedure iterations are typically at least every 1/29 to 1/30 second and more usually 1/29.97 second to 1/30 second. For PAL systems (systems used in parts of Europe, China and Hong Kong), the frame rate is 25 fps and thus interrupt procedure is substantially at least every 1/25 second. In general, the interrupt procedure should iterate close to the transfer rate or slightly

faster than the transfer rate, e.g. within at least 1/10th second of the transfer rate and more typically within 1/100th second. The iterations should not be slower than the transfer rate and the iterations are usually at the rate that corresponds to the frame rate of video standard.

5 Usually, the processing system according to the present invention, outputs the information, e.g. depicts the information on the display at a rate (the “output rate”) that is substantially similar to the rate in which each unit of the information, e.g. frame of video, is arriving from the information source (the “transfer rate”). In contrast with prior systems, where low quality displaying (i.e. considerably lower than
10 the transfer rate, such as 30 to 70% of the transfer rate) is used to devote more of the system to capture, the present invention may use high quality (i.e. the same or substantially similar to the transfer rate, such as greater than 70% and more usually 93 to 100% of the transfer rate) because all of the information is certain to be stored by the interrupt procedure. The speed at which the information is displayed depends on
15 numerous factors, such as side operations being simultaneously performed by the system, e.g. network access and CD ROM detection, image quality, e.g. based on decompression schemes employed, and processor speed or graphic acceleration. For example, where the transfer rate is about 30 frames per second (fps), the corresponding output rate of the present invention is usually 29 to 30 fps. The
20 transfer rate depends on the particular transfer rate standard employed, as described in detail below. The resulting capture output is of high quality that is similar to the quality of the information residing in the information source.

During the capture process, the time based stream of information is written into storage to be referenced while creating the presentation. For convenience, the
25 stored information may be compressed to conserve storage space. Generally, compression formats are either high efficiency or low efficiency and either loss-less or lossy. Lossy compression schemes are characterized by components of an original image being absent from a reconstructed image after a compression-decompression cycle, whereas loss-less schemes do not drop any information.

30 Low compression schemes (i.e., those that do not provide significant compression ratios) that may be used include joint photographic experts group (JPEG) compression schemes that use Fourier analysis-based methods, such as the discrete cosine transform, to compress data; graphics interchange format (GIF) compression schemes, which use LZW algorithms; bitmapped image compression schemes and

tagged image file format (TIFF) compression schemes, etc. Alternatively, high efficiency compression schemes, such as wavelet, motion wavelet, Motion Picture Experts Group (MPEG) motion JPEG, Lempel Ziv and/or fractal compression schemes, etc., may be employed. Use of high efficiency schemes may be preferred where storage space is limited. For example, wavelet compression schemes may be 20 times more efficient than JPEG compression schemes, providing for a more detailed representation of the data at the same bit budget. Once the time based information is captured and stored, it may be referenced for editing and generating a presentation.

The editing of stored information is often through the output, such as depiction on the display or playing on speakers, of capture information from the time based stream of information being acquired, process information useful in the editing process to produce the presentation, control elements, etc. Means for presenting the capture information, process information and control elements are provided.

The present invention additionally involves at least one and usually a plurality of control elements 72, e.g. objects, that may be visible (as shown in **Figure 2**) or invisible to the display. Control elements may be used to control the capture process or edit process. Control elements allow a user to manipulate and design a presentation or otherwise control it. The controls may be activated by the user or by other means, such as by software instructions, to create control commands. A user may activate control elements through input/output device 92. Input/output devices useful in activating control elements are keyboards, mouses, other cursor pointing devices, microphone, etc.

The control elements respond to activation by sending instructions to the processor. For example, a processing control element conveys directions to the processor regarding how a clip is to be treated or displayed. Each control element includes properties that describe how it will react when selected by the user or other means.

The processing system may contain any number of different types of control elements. One set of control elements are output controls 248 that implement how the user chooses to view or listen to the information from the system. Output control elements may direct the showing of the information on the monitor window 246, the playing of information through audio speakers, or output through other convenient

devices in communication with the system. There are several types of output controls 248 that may be provided by the processing system.

The output controls 248 may be used to move the play-head (i.e. pointer to indicate the location in the information available for use) to particular sections of the information stored in the storage. One such output control is a play control 250 that directs the system to play or show the information. Other kinds of output controls include a rewind control 252 and a forward control 254. The play-head may be jogged backward by the user depressing the rewind control 252 to shuttle the play-head in reverse direction. The output of information is advanced by the user selecting the forward control 254 during playback to shift forward at faster than the normal play rate, e.g. double the speed. Also provided by the processing system may be a stop control 256 for ceasing the output action and a pause control 258 for temporarily suspending the movement of the information from the system. In practice, the stop control 256 may be selected and then the rewind control 252 or forward control 254 selected to quickly skip forward or backwards through the footage.

In one method of outputting the time based information through the use of output controls, the play control 250 is activated and then the rewind control 252 or forward control 254 chosen to move to a position that is immediately prior to the appropriate position for capture. The stop control 256 is selected and the play control 250 is reactivated. When the scene of interest is displayed or a particular portion of audio is played, the clip may be edited.

Several additional output controls may also be employed for alternative ways of communicating the information. For example, a full screen mode control 152 may be provided to permit the presentation to be shown in a window that spans the entire area of the display. Also, some control elements may adjust the quality of playback. A preferences option with a playback tab (not shown), and an edit pull down menu 254 are some optional quality controls. In addition, a sound control knob 256 functions to adjust the intensity of audio.

A smooth motion control may be present to allow the user to create a smoother playback than would be typically expected. Usually, the bandwidth necessary to display digital video requires that visual quality be compromised in order to deliver a high number of frames per second (fps) during playback. Also, a better image control may be included to provide a crisper playback and more detail from each frame displayed. Such option for a better image is often at the expense of motion quality.

The number of frames per second that may be displayed is dependent on the processing power of the system, where higher power results in higher frame rate and less choppy playback.

Some forms of control elements that are visible on the screen are buttons, 5 "pop-up" or pull-down menus, scroll bars and iconic images. Other control elements may be invisible to the screen and thus are not included on the GUI. There are a variety of interactive mechanisms to activate the control elements, such as keyboard input, voice command, mouse manipulation, text entry, pen-to-text data entry device, touch screen, network signals, satellite transmissions, preprogrammed triggers within 10 the system, instructional input from other applications, etc. All of the control elements described herein are by way of example and are not intended to limit the choices that are or may become available in the art.

Other control elements are not visible on the screen but may be present on 15 input/output devices, such as a keyboard that is in communication with the I/O control. For example, a space bar on a keyboard may also be depressed to start capture and depressed again to stop capture of the information on the fly while playing the time based information during capture mode.

The table shown below describes other control elements that may be present 20 on the keyboard, where the items in the "action" column describe the command activated by depressing the keyboard button and the items in the "shortcut" column are the corresponding keyboard buttons.

Keyboard shortcuts Navigation

Action	Shortcut
--------	----------

Play/Stop and Start/Stop Capture Space Bar

Play-head to Beginning of Home

Movie

Play-head to End of Movie End

Forward One Frame Right Arrow

Forward Ten Frames Shift + Right Arrow

Roll Play-head Forward	Hold Down Right Arrow
Search Forward (fforward)	Command +]
Back One Frame	Left Arrow
Back Ten Frames	Shift + Left Arrow
Roll Play-head Backward	Hold Down Left Arrow
Search Backward (rewind)	Command + [
Selection	
Action	Shortcut
Multiple Selection	Shift + Click Item
Multiple Selection (range)	Click 1st item then Shift + Click last item
Moving/Cropping	
Action	Shortcut
Move Audio Clip	Click Clip + Left or Right Arrow
Move Audio Clip Ten Frames	Click Clip, then Shift +Left or Right Arrow
Move Crop Marker	Click Marker + Left or Right Arrow
Move Crop Marker Ten Frames	Marker, then Shift +Left or Right Arrow
Accept/Cancel	

Action	Shortcut
Accept Dialogs (OK)	Return
Cancel Dialogs	Esc or Command + C
Cancel Rendering	Command + . (period)
Volume	
Action	Shortcut
Increase System Volume	Up Arrow
Decrease System Volume	Down Arrow
Titling	
Action	Shortcut
Move Between Text Fields	Tab
File Menu Functions	
Action	Shortcut
New Project	Command + N
Open Project	Command + O
Save Project	Command + S
Export Movie	Command + E
Save Frame As	Command + F
Import File	Command + I

Quit Command + Q

Edit Menu Functions

Action	Shortcut
Undo	Command + Z
Redo	Shift + Command + Z
Cut	Command + X
Copy	Command + C
Paste	Command + V
Crop	Command + K
Split Clip at Play-head	Command + T
Select All	Command + A
Select None	Command + D

Help Menu Functions

Action	Shortcut
Imovie Help	Command + ? or Help key

- 5 The visible control elements as well as other editing data may be depicted on a graphical user interface (GUI) on the display. An exemplary GUI **230** for displaying various data related to both the capture of the information and processing of the information is depicted variously in **Figures 6A to 6C**. The GUI has numerous innovations that allow a user to easily make edits and create a presentation.

As shown in **Figure 6A**, the process information displayed on the GUI 230 may include at least one object reference element 236, e.g. icon, with each reference element 236 being associated with a reference in storage that has data for a clip of the time based information contained in storage 30. Typically, the reference element 236 5 is displayed as a “thumbnail” in the form of a still image of the first frame of the associated clip. Where the reference has an edit feature, a description or depiction of the edit feature may also be included. Some reference having edit features may have a thumbnail image associated with the corresponding clip and along with a portrayal of the edit feature 350. Other edit features may have a particular shape, size or texture to 10 indicate the edit feature. For example, a reference to a transition may be in the form of a box 352.

The process information may also include an edit output to reveal stored clips of the time based information for processing/editing during an edit mode. The edit output may depict how the clips would appear in presentation after editing is 15 complete. For example, the user may desire to modify a clip, such as add a title or transition to a clip, via a reference with an edit feature. The user may observe the edit output of the clip with the selected title or transition and the user may choose to accept or reject the modification.

Typically, one or more windows are present in the GUI, which may be opened 20 by processor 24 or by the user. One such user interface illustrated in **Figure 6A** has several windows, such as a monitor window 246, time line 240 and edit box 268. The monitor window 246 may be the viewing portion of the display that shows the edit output. Various other windows may be present on the display of the processing system to provide at least one control element.

The user may input commands to relocate reference elements 236 to the 25 several windows and portions on the GUI, such as a shelf 238, a video time line 240, an audio time line 242 or other portion of the display, in order to manipulate the references in forming segments of a presentation. By selecting the reference element(s) or portion thereof, and employing other process information, the reference 30 element or portions of reference elements, may be moved around the GUI 230 and edited. One typical way for a user to select a reference element is by pointing a cursor on the reference element and clicking on it, such as via a mouse or keyboard stroke. However, a user may use other tools for selection such as menu choices, voice

instructions, etc. A selected reference may be indicated on the GUI by a highlighted border 354 around the reference.

In one embodiment, a reference element is moved to various portions of the display by moving a pointer 356, e.g. cursor, over the reference element and dragging the reference element to another portion of the display. The reference element is dropped over the intended spot on the GUI by releasing the pointer from the reference element.

Another means to move a reference element is though a cut and paste command. The reference element is selected and is made to disappear from the screen by activating a cut command. Activation of the cut command may occur by the user choosing a menu option, keyboard stroke, etc. An intended place for the relocation is selected and a paste command activated to prompt the reference element to reappear in the selected place.

In addition, other functionalities may be provided by the processing system to relocate the reference element on the GUI, such as mouse clicks, keyboard commands, menu options, various types of control elements, etc.

Other process information displayed on the GUI 230 may also include at least one control element for the user to manipulate the time based information and construct a presentation, at least one time line that represents the edited presentation, such as a graphical representation of a visual time line 240 and a graphical representation of an audio time line 242, and other elements that add convenience to the edit process.

The reference to each clip that is to be included in the presentation is positioned in the presentation by arranging the reference element(s) along a visual time line 240 in the order that the associated information will appear in the presentation. The visual time line 240 is for adding visual information, such as the time based stream of information in the form of full motion images, e.g. video and movies, motion graphics, e.g. animation, as well as still images, e.g. text, pictures, combinations thereof, and the like. The audio time line 242 is for including audio information, such as music, sound effects, and voice/narration, etc. to the presentation. The data corresponding to the time line is stored in presentation storage area within the system.

According to the present invention, the processing system includes functionality to display and use only a single visual time line 240 which is capable of

handling any type of edit feature and other visual information. Thus, the one time line may include visual reference elements with any combination of the edit features to be included in the presentation. Where it is desired for an edit feature it be nested in another reference (i.e. clip), the reference element is split into two reference elements

- 5 and the reference element having the edit feature is positioned between the two on the time line. A time code 237 may be provided that indicates the length of a clip associated with the reference. Furthermore, the time line may include the total time 358 of the presentation. The time line also may have a scroll bar 360 to move up and down the length of the time line, so that the time line is not limited by the space
10 provided by the display. This limit of one visual time line simplifies the GUI, allows for easy interpretation of the edits made to the presentation, conserves storage space (that may be otherwise squandered on several visual time lines for various edit features) and spares the GUI of wasted areas, and other such benefits.

- 15 At any time during the edit process, the clip associated with a reference element may be viewed on a monitor window 246. To view the information, a reference element may be selected and dragged/dropped or cut/pasted onto the monitor window. However, such these actions do not necessarily result in the reference element being removed from its current place on the GUI, but simply allow the information to appear on the monitor window.

- 20 A monitor window time ruler 260 depicts where the play-head 262 as it travels along the course of the clip. A variety of output controls 248 may be used to move the play-head to various positions on the clip. When the play-head is at the frame of interest, the pause control 258 may be activated and the frame edited. In this manner, particular portions of information may be selected by the user and the system may be
25 further instructed to edit the selected portion, e.g. deleting the selected portion from storage.

- Edit features may be conveniently added by use of an edit box 268 that includes various editing control options, such as titles control 270, transitions control 300, music control 330 and sound control 350. Specific sub-windows having edit
30 controls may be included for the various edit features contained in the edit box. The sub-windows may pop-up on the GUI by activating, e.g. by a mouse click, one of the edit control options. The sub-windows may also be retrieved by selecting an existing reference that has an edit feature. Upon selecting such as reference, the sub-window to its edit feature automatically appears on the screen and is ready for further editing.

These pop-up windows save screen space and create an easy editing environment for the user.

Title control 270 includes instructions for adding text, such as headings, labels or captions, to a clip. Selection of the title control 270 opens a title window 274 as shown in **Figure 6B**. A transition time ruler 276 shows the length of the selected clip and the position of the play-head 278. The user may navigate the play-head to various frames in the clip by positioning a cursor over the play-head by use of a mouse, or using other cursor positioning means. The mouse may be used by clicking and holding down on it and sliding the mouse to the left or right along the title time-line relative to the desired location of the play-head.

The title window 274 also includes one or more text field 280 for creating text to be inserted in the clip. A position menu 282 permits the user to choose where and how the text is to appear on the frame. For example, the text may be a centered title, appear to bounce through the length of the frame, centered with multiple text lines, centered as a title, letters flying across the frame, words flying, music video, rolling center credits, rolling credits, scroll with a pause, scrolling as a block, typewriter, and the like. A font menu 288 may be used to dictate the character type. An “over black” control 284 is used to insert an additional black frame at the play-head position and the title over the black frame. An example of a reference element with text over black 285, having the title, “THE END” is shown on time line 240. On the other hand, a “color” control 286 may be used to overlay the text over the current frame. The text may be shown in a preview window 290 by selecting a preview control 292. Preview simulates the edited reference without the edited version being actually saved in storage. An add control 294 is for storing the reference with the title. The reference with edit feature 296 may then be shown on the monitor window 246. The initial clip 01 may be split into the reference with edit feature 296 and remaining portion reference 298, as shown on video time line 240.

A transition control 300 has instructions for inserting an effect between clips, where selection of the transition control 300 opens a transition window 302, as depicted in **Figure 6C**. A transition effects menu 304 permits the user to choose from any one of numerous transition options. Examples of transitions are cross dissolve, cross dissolve slow, fade in, fade out, overlap, push right, slowly push right, scale down, slowly scale down, and the like. The frame location of the play-head 314 along transition time ruler 316 may be positioned by the same or similar manner as

described above for introducing titles in a clip. The transition is typically inserted as a frame immediately after the play-head position by reference element with transition 352 and then appears on visual time line 240.

Furthermore, edit box 268 shown in **Figure 6A** includes music control 330 for

- 5 incorporating music tracks to the presentation where the music may be recorded by controls in the music control window. Sound control 350 in the edit box 268 is for including sound effect to portions of the presentation. Usually, the sound effects are prerecorded and stored within the processing system. Some examples of sounds are cat meow, dog bark, crickets, crowd applause, trumpets fanfare, wild laugh, water lapping, whistle, thunder, horn honk and footsteps.

During the edit process, the user may make use of the tools described above in a variety of ways to form the desired presentation. Typically, references are selected, viewed, optionally modified with edit features and transferred to a position on the time line, such as by drag/drop or cut/paste mechanisms. For example, a reference

- 15 may be selected from the monitor window of an edit sub-window and either cut and pasted into the time line or dragged from the monitor window and dropped into the time line. At any time, particular references may be removed from the presentation and returned to the shelf, also through the drag and drop or cut and paste tools. Where a reference is removed, the references remaining in the presentation shift over in the time line to create a seamless continuation of the presentation.

In addition, where a user does not need a segment of information for the presentation, a clip or portion of a clip may be removed from storage. Entire clips or portions of clips may be deleted by selecting the reference data and dragging it to the trash icon control 370. After depositing the reference data in the trash, the user may

- 25 activate a delete control. For example, the user may select an "empty trash" e.g. from a pull down menu. In still other embodiments, the user may activate a "cut" command, e.g. from a pull down menu, to have the selected data placed on a paste board. The user may then send delete instructions to the processing system and the data as well as corresponding information is deleted. In another embodiment, an intermediary trash bin or paste board is not used and the user simply elects to delete selected reference data. Other methods for the user to send selection, deletion and trash commands are also possible and intended by the present invention.

The presentation, as edited, may be saved in a variety of formats, such as a QuickTime file or other formats suitable for transfer via e-mail, web pages, CD-

ROM, etc. The presentation may be accessed at a later time for additional editing or may be transferred from the processing system, such as conveyed to an external player.

- The capture information presented on the GUI is related to the time based information being acquired by the system while in capture mode. The capture information may include a depiction or replay of the time based stream of information (referred to as a “capture output”), as well as other characteristics of the information that is being acquired. The capture output sets forth the current frames that are being received and read, such as newly acquired information that is present in a proxy, i.e. buffer, prior to being written into storage. During the capture mode, the monitor window 246 may exhibit the capture output of the time based information. In addition to showing the capture output, the monitor window 246 may depict the edit output, usually where the capture output is shown while the information is acquired and the edit output is shown while editing the presentation. By this dual use of the monitor window, the screen area is conserved and the user interface is simplified.

- A time code 237 may also be provided as capture information to indicate the length of a clip. In addition, the capture information may include an audio synch time line 242 on which references to clips 236 are arranged and depicted in size according to the length of the clip in storage for use in adding audio portions to a presentation. A user may opt for the audio synch time line to automatically display the references for each incoming stream of information. For example, the user may choose a preferences control from a menu and select to have the references appear in the audio synch time line rather than the shelf portion of the user interface. The capture information may further include a space monitor element 234 to show the amount of storage space remaining or amount of space consumed by stored information. Capture information may also include tools, e.g. control elements, for controlling the capture process.

- The present invention frequently has a single GUI to display enabled, i.e. operable, capture information and enabled, i.e. operable, process information. Such a GUI is functional for both capture and edit procedures, thus avoiding the necessity of switching to multiple GUI's to view and work with information relating to capture and information relating to the processing of the presentation. Any convenient portions of the screen may be used to show the capture and process information without the user needing to toggle between screens. In one instance, a portion of the

display provides capture information, such as the capture output, and another portion of the display contains process information. An example of this embodiment is where capture information is shown in a window on the display, and process information in at least one other window on the display. In the alternative, the same portion of the display may be used to show capture information and process information at different times. In one such embodiment, a capture output may be presented on a viewing portion of the display during capture of the time based information and an edit output may be presented on the same viewing portion during editing of the presentation.

In addition to the features described above, the processing system may further include alternative aspects that enhance ease and convenience of use. For example, referring again to **Figure 2**, the information source **80** may be controlled through the processing system **12**. Source controls operate the information source **80**, usually where no digital converter **82** is employed as an intermediate between the information source and processing system. The source controls may be presented on the GUI. In one embodiment, the output controls **248**, as shown in **Figure 6A** also serve as the source controls to direct the monitor window views at one time and send action commands to the information source **80** at another time. Thus, the source controls may include rewind control **252**, forward control **254**, play control **250**, pause control **258** and stop control **256**.

20 SOFTWARE OVERVIEW

Various software components may be provided within or in communication with the system that cause the processor to execute the numerous methods employed in creating the presentation. **Figure 7** is a block diagram of a machine-readable medium storing executable code and/or other data to provide one or a combination of mechanisms for manipulating the time based stream of information, according to one embodiment of the invention. The machine-readable storage medium **400** represents one or a combination of various types of media/devices for storing machine-readable data, which may include machine-executable code or routines. As such, the machine-readable storage medium **400** could include, but is not limited to one or a combination of a magnetic storage space, magneto-optical storage, tape, optical storage, dynamic random access memory, static RAM, flash memory, etc.

The machine readable storage medium **400** is shown storing a GUI routine **402**, which, when executed, provides a GUI for display of capture and process information regarding the time based stream of information, such as the GUI **230**

shown in **Figures 6A-6C**. The GUI routine **402** includes a number of mechanisms for playing or otherwise processing the time based stream of information. For example, a show visual time line routine **404** provides the time line representation of the presentation storage area and references placed therein, as described with regards to
5 **Figures 6A- 6C**. A present process information routine **406** provides process information and present control elements **408** permits control elements to be visible on the display.

The medium **400** also has a process control command routine **418** that directs the carrying out of various commands, such as for manipulating information and
10 constructing a presentation. The control commands may be generated by activation of control elements by the user. Upon receipt of the control commands, the process control command **418** may send instructions to the GUI Routine **402** to specify particular information to be presented or manner of presenting information. The process control command **418** routine may also send the commands to a process
15 management routine, such as an add edit feature command, undo command, delete command, select information command, cancel delete command, and the like, as described below.

The medium also has a process management routine **410** that may have various subroutines for conducting various tasks related to editing and carrying out
20 instructions from the process control command routine **418**. One such subroutine is a cut/copy/paste subroutine **412**, which when executed, references or portions thereof are cut, copied and/or pasted into a presentation. The process management routine **410** may be also configured for conducting an add edit feature subroutine **416** to include particular edit features to references for use in a presentation. An undo edit subroutine
25 **414** may optionally be included whereby certain edit tasks may be undone to reclaim the unmodified version of data

Other software components may include an operating system **420** and a presentation transfer routine **422** that facilitates communication of information from the processing system, such as via external player **84**. Various modes of transfer are
30 described above with reference to the external player **84** in **Figure 2**.

The software components may be provided in as a series of computer readable instructions that may be embodied as data signals in a carrier wave. When the instructions are executed, they cause a processor, such as through a browser to perform the capture and editing steps as described. For example, the instructions may

cause a processor to communicate with an information source, provide capture information from the time based stream of information on a first portion of a display, provide process information for constructing the presentation on a second portion of the display; and provide at least one enabled control element. Such instructions may

- 5 be presented to the processor by various mechanisms, such as a plug-in, ActiveX control, through use of an applications service provided or a network, etc.

The present invention has been described above in varied detail by reference to particular embodiments and figures. However, these specifics should not be construed as limitations on the scope of the invention, but merely as illustrations of some of the presently preferred embodiments. It is to be further understood that other modifications or substitutions may be made to the described information transfer system as well as methods of its use without departing from the broad scope of the invention. Therefore, the following claims and their legal equivalents should determine the scope of the invention.

CLAIMS

What is claimed is:

1 1. A method for processing a presentation of a time based stream of information,
2 the method comprising:

- 3 A) providing a user interface having functionality to display only a
4 single graphical representation of a time line for positioning at
5 least one reference to a visual time based stream of information
6 in a presentation, the reference including one or at least two
7 types of edit features;
- 8 B) displaying the single graphical representation of a time line on
9 the user interface;
- 10 C) displaying a reference with an edit feature on the user interface;
11 and
- 12 D) dragging the reference over the single graphical representation
13 of the time line to insert the edit feature into the presentation.

14 2. The method of claim 1, wherein the edit feature is text.

15 3. The method of claim 1, wherein the edit feature is a transition.

16 4. The method of claim 1, wherein the single graphical representation of a time
17 line includes at least two references and wherein the reference with an edit
18 feature is dragged between the two references.

19 5. The method of claim 1, wherein providing the reference with the edit feature is
20 by moving a reference to an edit box and inserting the edit feature into the
21 reference in response to user edit commands.

22 6. The method of claim 5, wherein the moving of the reference is by cutting the
23 reference and pasting the reference over the edit box.

1 7. The method of claim 1, further including editing the edit feature of the
2 reference by selecting the reference and popping up an edit box automatically
3 in response to the selecting.

4 8. The method of claim 1, further including displaying another reference having
5 an edit feature and in response to a user cut/paste command, cutting the other
6 reference from a position on the user interface and pasting the other reference
7 over the single graphical representation of the time line to insert the edit
8 feature into the presentation.

9 9. The method of claim 8, wherein the single graphical representation of a time
10 line includes at least two references and wherein the reference having an edit
11 feature is pasted between the two references.

12 10. A method for processing a presentation of a time based stream of information,
13 the method comprising

14 A) providing a user interface having functionality to display only a
15 single graphical representation of a time line for positioning at
16 least one reference to a visual time based stream of information
17 in a presentation, the reference including one of at least two
18 types of edit features;

19 B) displaying the single graphical representation of a time line on
20 the user interface;

21 C) displaying a reference having an edit feature on the user
22 interface; and

23 D) cutting the reference from a position on the user interface and
24 pasting the other reference over the single graphical
25 representation of the time line to insert the edit feature into the
26 presentation.

27 11. The method of claim 10, wherein the edit feature is text.

28 12. The method of claim 10, wherein the edit feature is a transition.

- 1 13. The method of claim 10, wherein the single graphical representation of a time
- 2 line includes at least two references and wherein the reference with an edit
- 3 feature is dragged between the two references.
- 4 14. The method of claim 10, wherein providing the reference with the edit feature
- 5 is by cutting and pasting a reference to an edit box and inserting the edit
- 6 feature into the reference in response to user edit commands.
- 7 15. The method of claim 10, further including editing the edit feature of the
- 8 reference by selecting the reference and popping up an edit box automatically
- 9 in response to the selecting.
- 10 16. A digital processing system comprising:
 - 11 A) a capture port for acquiring a time-based stream of information;
 - 12 B) a storage;
 - 13 C) a display device; and
 - 14 D) a processor for:
 - 15 (i) providing a user interface having functionality to
 - 16 displaying only a single graphical representation of a time
 - 17 line for positioning at least one reference to a visual
 - 18 time based stream of information in a presentation, the
 - 19 reference including one of at least two types of edit
 - 20 features;
 - 21 (ii) displaying the single graphical representation of a time
 - 22 line on the user interface;
 - 23 (iii) displaying a reference with an edit feature on the user
 - 24 interface; and
 - 25 (iv) dragging the reference over the single graphical
 - 26 representation of the time line to insert the edit feature
 - 27 into the presentation.
- 28 17. The system of claim 16, wherein the edit feature is text.

004860.P2474 88300100

- 1 18. The system of claim 16, wherein the single graphical representation of a time
2 line includes at least two references and wherein the reference with an edit
3 feature is dragged between the two references.
- 4 19. The system of claim 16, wherein the providing the reference with the edit
5 feature is by moving a reference to an edit box and inserting the edit feature
6 into the reference in response to user edit commands.
- 7 20. The system of claim 19, wherein the moving of the reference is by cutting the
8 reference and pasting the reference over the edit box.
- 9 21. The system of claim 16, further including editing the edit feature of the
10 reference by selecting the reference and popping up an edit box automatically
11 in response to the selecting.
- 12 22. The processing system for generating a presentation of a time-based stream of
13 information comprising:
 - 14 A) means for providing a user interface having functionality to
15 display only a single graphical representation of a time line for
16 positioning at least one reference to a visual time based stream
17 of information in a presentation, the reference including one of
18 at least two types of edit features;
 - 19 B) means for displaying the single graphical representation of a
20 time line on the user interface;
 - 21 C) means for displaying a reference with an edit feature on the
22 user interface; and
 - 23 D) means for dragging the reference over the single graphical
24 representation of the time line to insert the edit feature into the
25 presentation.
- 26 23. The system of claim 22, wherein the edit feature is text.


- 1 24. The system of claim 22, wherein the single graphical representation of a time
2 line includes at least two references and wherein the reference with an edit
3 feature is dragged between the two references.
- 4 25. The system of claim 22, wherein the providing the reference with the edit
5 feature is by moving a reference to an edit box and inserting the edit feature
6 into the reference in response to user edit commands.
- 7 26. The system of claim 25, wherein the moving of the reference is by cutting the
8 reference and pasting the reference over the edit box.
- 9 27. The system of claim 22, further including means for editing the edit feature of
10 the reference by selecting the reference and popping up an edit box
11 automatically in response to the selecting.
- 12 28. A computer readable medium having stored therein a plurality of sequences of
13 executable instructions, which, when executed by a processing system for
14 collecting a time based stream of information and generating a presentation,
15 cause the processor to:
 - 16 A) provide a user interface having functionality to display only a
17 single graphical representation of a time line for positioning at
18 least one reference to a visual time based stream of information
19 in a presentation, the reference including one of at least two
20 types of edit features;
 - 21 B) display the single graphical representation of a time line on the
22 user interface;
 - 23 C) display a reference with an edit feature on the user interface;
24 and
 - 25 D) drag the reference over the single graphical representation of
26 the time line to insert the edit feature into the presentation.
- 27 29. The computer readable medium of claim 28, wherein the edit feature is text.

- 1 30. The computer readable medium of claim 28, wherein the single graphical
2 representation of a time line includes at least two references and wherein the
3 reference with an edit feature is dragged between the two references.
- 4 31. The computer readable medium of claim 28, wherein the providing the
5 reference with the edit feature is by moving a reference to an edit box and
6 inserting the edit feature into the reference in response to user edit commands.
- 7 32. The computer readable medium of claim 31, wherein the moving of the
8 reference is by cutting the reference and pasting the reference over the edit
9 box.
- 10 33. The computer readable medium of claim 28, further including additional
11 sequences of executable instructions, which, when executed by the processor,
12 cause the processor to edit the edit feature of the reference by selecting the
13 reference and pop up an edit box automatically in response to the selecting.

ABSTRACT

A method of manipulating a time based stream of information through use of a user interface to generate a presentation is provided in which a processing system is employed. The methods use references to a selected time based stream of information

- 5 as editing tools. The user interface has functionality to display only a single time line for aligning reference elements to visual time based stream of information. The references may include a variety of edit features that enhance the presentation. Some mechanisms for moving the reference elements on the user interface are drag and drop and/or cut and paste procedures. Other aspects of the present invention relating to the
- 10 processing system providing convenient user interface and editing tools for use in authoring a presentation of a time based stream of information are also described.



PRIOR ART

FIGURE 1




FIGURE 2

000010100000000000000000




FIGURE 3




Figure 4A




Figure 4B




Figure 4C

Figure 5A





Figure 5B










FIGURE 6A





00010010-00020000-0000-00000000




FIGURE 7

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below, next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

INTEGRATED TIME LINE FOR EDITING

the specification of which

X is attached hereto.
____ was filed on _____ as
United States Application Number _____
or PCT International Application Number _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above. I do not know and do not believe that the claimed invention was ever known or used in the United States of America before my invention thereof, or patented or described in any printed publication in any country before my invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months (for a utility patent application) or six months (for a design patent application) prior to this application.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d), of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Docket # 004860

Prior Foreign Application(s)			Priority Claimed	
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
			Yes	No
			Yes	No
			Yes	No

I hereby claim the benefit under title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below:

(Application Number) _____ Filing Date _____

(Application Number) _____ Filing Date _____

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Number) Filing Date (Status -- patented,
pending, abandoned)

I hereby appoint the persons listed on Appendix A hereto (which is incorporated by reference and a part of this document) as my respective patent attorneys and patent agents, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

Send correspondence to Lisa N. Benado, BLAKELY, SOKOLOFF, TAYLOR & (Name of Attorney or Agent)
ZAFMAN LLP, 12400 Wilshire Boulevard 7th Floor, Los Angeles, California 90025 and direct telephone calls to Lisa N. Benado, (408) 720-8589.
(Name of Attorney or Agent)

INVENTOR'S STATEMENT

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole/First Inventor Glenn Reid

Inventor's Signature _____ Date _____

Residence _____ Citizenship _____
(City, State) (Country)

Post Office Address _____

Full Name of Second/Joint Inventor _____

Inventor's Signature _____ Date _____

Residence _____ Citizenship _____
(City, State) (Country)

Post Office Address _____

Full Name of Third/Joint Inventor _____

Inventor's Signature _____ Date _____

Residence _____ Citizenship _____
(City, State) (Country)

Post Office Address _____

Full Name of Fourth/Joint Inventor _____

Inventor's Signature _____ Date _____

Residence _____ Citizenship _____
(City, State) (Country)

Post Office Address _____

APPENDIX A

William E. Alford, Reg. No. 37,764; Farzad E. Amini, Reg. No. P42,261; Aloysius T. C. AuYeung, Reg. No. 35,432; William Thomas Babbitt, Reg. No. 39,591; Carol F. Barry, Reg. No. 41,600; Jordan Michael Becker, Reg. No. 39,602; Bradley J. Bereznak, Reg. No. 33,474; Michael A. Bernadicou, Reg. No. 35,934; Roger W. Blakely, Jr., Reg. No. 25,831; Gregory D. Caldwell, Reg. No. 39,926; Andrew C. Chen, Reg. No. 43,544; Thomas M. Coester, Reg. No. 39,637; Dennis M. deGuzman, Reg. No. 41,702; Stephen M. De Clerk, under 37 C.F.R. § 10.9(b); Michael Anthony DeSanctis, Reg. No. 39,957; Daniel M. De Vos, Reg. No. 37,813; Robert Andrew Diehl, Reg. No. 40,992; Sanjeet Dutta, Reg. No. P46,145; Matthew C. Fagan, Reg. No. 37,542; Tarek N. Fahmi, Reg. No. 41,402; Paramita Ghosh, Reg. No. 42,806; James Y. Go, Reg. No. 40,621; James A. Henry, Reg. No. 41,064; Willmore F. Holbrow III, Reg. No. P41,845; Sheryl Sue Holloway, Reg. No. 37,850; George W Hoover II, Reg. No. 32,992; Eric S. Hyman, Reg. No. 30,139; William W. Kidd, Reg. No. 31,772; Sang Hui Kim, Reg. No. 40,450; Eric T. King, Reg. No. 44,188; Kurt P. Leyendecker, Reg. No. 42,799; Michael J. Mallie, Reg. No. 36,591; Andre L. Marais, under 37 C.F.R. § 10.9(b); Paul A. Mendonsa, Reg. No. 42,879; Chun M. Ng, Reg. No. 36,878; Thien T. Nguyen, Reg. No. 43,835; Thinh V. Nguyen, Reg. No. 42,034; Dennis A. Nicholls, Reg. No. 42,036; Daniel E. Ovanezian, Reg. No. 41,236; Marina Portnova, Reg. No. P45,750; Babak Redjani, Reg. No. 42,096; William F. Ryann, Reg. No. 44,313; James H. Salter, Reg. No. 35,668; William W. Schaal, Reg. No. 39,018; James C. Scheller, Reg. No. 31,195; Jeffrey Sam Smith, Reg. No. 39,377; Maria McCormack Sobrino, Reg. No. 31,639; Stanley W. Sokoloff, Reg. No. 25,128; Judith A. Szepesi, Reg. No. 39,393; Vincent P. Tassinari, Reg. No. 42,179; Edwin H. Taylor, Reg. No. 25,129; John F. Travis, Reg. No. 43,203; Joseph A. Twarowski, Reg. No. 42,191; Lester J. Vincent, Reg. No. 31,460; Glenn E. Von Tersch, Reg. No. 41,364; John Patrick Ward, Reg. No. 40,216; Mark L. Watson, Reg. No. P46,322; Thomas C. Webster, Reg. No. P46,154; Charles T. J. Weigell, Reg. No. 43,398; Kirk D. Williams, Reg. No. 42,229; Steven D. Yates, Reg. No. 42,242; and Norman Zafman, Reg. No. 26,250; my patent attorneys, and Justin M. Dillon, Reg. No. 42,486; my patent agent, of BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP, with offices located at 12400 Wilshire Boulevard, 7th Floor, Los Angeles, California 90025, telephone (310) 207-3800, and James R. Thein, Reg. No. 31,710, my patent attorney. I also hereby appoint Albert P. Cefalo, Reg. No. 27,315; Mark Aaker, Reg. No. 32,667; Richard Liu, Reg. No. 34,377; Helene Plotka Workman, Reg. No. 35,981; and Edward W. Scott, IV, Reg. No. 38,000; my attorneys; of APPLE COMPUTER, INC., located at 1 Infinite Loop, MS: 3-PAT, Cupertino, California 95014, telephone (408)974-9453, will full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith.

APPENDIX B

Title 37, Code of Federal Regulations, Section 1.56
Duty to Disclose Information Material to Patentability

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclosure information exists with respect to each pending claim until the claim is cancelled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is cancelled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) Prior art cited in search reports of a foreign patent office in a counterpart application, and
- (2) The closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made or record in the application, and

- (1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim; or
- (2) It refutes, or is inconsistent with, a position the applicant takes in:
 - (i) Opposing an argument of unpatentability relied on by the Office, or
 - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

- (1) Each inventor named in the application;
 - (2) Each attorney or agent who prepares or prosecutes the application; and
 - (3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.
- (d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.